

# Reliable use of smart cameras for monitoring biometric parameters in buffalo precision livestock farming

Roberta Matera<sup>1</sup>, Leopoldo Angrisani<sup>2</sup>, Gianluca Neglia<sup>1</sup>, Angela Salzano<sup>1</sup>, Francesco Bonavolontà<sup>2</sup>, Maria Teresa Verde<sup>2</sup>, Nadia Piscopo<sup>1</sup>, Domenico Vistocco<sup>3</sup>, Oscar Tamburis<sup>1,4</sup>

<sup>1</sup> Dept. of Veterinary Medicine and Animal Productions, University of Naples Federico II, Via F. Delpino 1, 80137 Naples, Italy

<sup>2</sup> Dept. of Electrical Engineering and Information Technology, Center for Advanced Metrological Systems (CeSMA), University of Naples Federico II, Str. Vicinale Cupa Cintia 21, 80126 Naples, Italy

<sup>3</sup> Dept. of Political Sciences, Communications and International Relationships, University of Naples Federico II, Via L. Rodinò 22, 80138 Naples, Italy

<sup>4</sup> Institute of Biostructures and Bioimaging, National Research Council of Italy, via T. De Amicis 95, 80145 Naples, Italy

## ABSTRACT

Precision Livestock Farming, as a specific sub-sector of Public Health Informatics, focuses on the application of process engineering principles and techniques to achieve an automatic monitoring, modelling, and management of animal productions. In the present work a timely "protocol" is proposed for unobtrusive direct/indirect monitoring of biometric parameters for the estimation of body conditions on Mediterranean Buffalo populations, using low-cost automated systems already present on the market i.e., smart cameras endowed with depth perception capabilities.

## Section: RESEARCH PAPER

**Keywords:** Public Health Informatics; precision livestock farming; measurement; mediterranean buffalo; smart cameras; 3D/2D image analysis

**Citation:** Roberta Matera, Leopoldo Angrisani, Gianluca Neglia, Angela Salzano, Francesco Bonavolontà, Maria Teresa Verde, Nadia Piscopo, Domenico Vistocco, Oscar Tamburis, Reliable use of smart cameras for monitoring biometric parameters in buffalo precision livestock farming, Acta IMEKO, vol. 12, no. 4, article 39, December 2023, identifier: IMEKO-ACTA-12 (2023)-04-39

**Section Editor:** Francesco Lamonaca, University of Calabria, Italy

**Received** August 14, 2023; **In final form** November 10, 2023; **Published** December 2023

**Copyright:** This is an open-access article distributed under the terms of the Creative Commons Attribution 3.0 License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

**Corresponding author:** Oscar Tamburis, e-mail: [oscar.tamburis@ibb.cnr.it](mailto:oscar.tamburis@ibb.cnr.it)

## 1. INTRODUCTION

As widely reported in the literature, the Public Health (PH) sector encompasses several important disciplines, such as epidemiology, biostatistics, and environmental science. Among the latest and most critical progresses registered in PH, (i) One Health is a transdisciplinary approach that recognizes the connection between people's health, animal health, and the surrounding environment, while (ii) Public Health 3.0 addresses the collaboration necessary to achieve that integration [1].

In the wake of this, the "systematic application of information and computer science and technology to PH practice, research, and learning" [2] is referred to as Public Health Informatics (PHI), which stands among the sub-areas of the overarching BioMedical and Health Informatics (BMHI) field [3]. In this scenario, as concerns globally raise especially about environmental sustainability and animal welfare, Precision Livestock Farming (PLF) is reported as a declination of PHI

focused on the application of process engineering principles and techniques to livestock farming, in order to an automatic monitoring, modelling, and management of animal production.

PLF's primary goal is to make livestock farming more economically, socially, and environmentally sustainable, thus pursuing surveillance, reporting, and health promotion goals [4], [5]. Awareness is therefore rising worldwide as to the importance of a systematic deployment, by means of smart computing and sensing technologies, of integrated (and economically sustainable) solutions for continuous monitoring of quality and salubrity of the production environments. The scope is to achieve an integrated vision between production characteristics, animal welfare, and security issues. In particular, the adoption of new types of approaches for weight assessment aims to increase the accuracy of measurement and, accordingly, to improve the monitoring of animal performance, thus potentially providing major benefits to both the herdsmen and the animals in their care [6]-[8].

About one ninth of the global cattle population is composed by an essential domestic bovid, the so-called water (or river) buffalo (*Bubalus bubalis*), also known as Asian buffalo. The 3% of such population is represented by the Mediterranean buffalo. In 2001 the Italian Ministry of Agriculture and Forestry, thanks to long isolation and lack of crossbreeding with other strains, further recognized the "Mediterranean Italian buffalo" breed [9]. In South Italy the whole Buffalo-related dairy production and supply chain represents a leading sector of the entire Agri-food arena. Although understudied if compared with other cattle breeds, the information on body weight prediction in Mediterranean buffaloes is of great importance for making much better decisions as to breed standards, breeding schemes, flock management, and conserving gene reserves [10], [11].

The present study aims therefore to propose, formalize and test a "protocol" for unobtrusive direct/indirect monitoring of biometric parameters for the estimation of body conditions on Mediterranean Buffalo populations, using low-cost automated systems already present on the market i.e., smart cameras endowed with depth perception capabilities. In particular, a set of Machine Learning-based algorithms (linear regressions; neural networks) were deployed on the set of measurements obtained by a combination of three different devices – a photcamera, a Depth Camera, and a LiDAR Camera – compared with traditionally hand-performed measurements on Mediterranean Buffalo calves from the birth to their complete weaning. The goal is twofold: (i) Figure out the most timely measurement tools to be used to correctly estimate and predict the weight trajectories; and (ii) verify whether the adoption of an electronic measurement system can lead to best practices in Precision Livestock Breeding.

The paper is organized as follows: after the introduction, a brief view is provided as to cattle monitoring systems, and the many phases of the experimental design are reported; results are therefore described, and some discussion and conclusions are eventually indicated.

## 2. STATE OF THE ART

### 2.1. (Technology-enabled) cattle monitoring systems

Calves rearing, especially during the first period of life, is one of the most delicate phases of the entire production process in a dairy farm, for both bovine and buffalo species. Inadequate nutrition or unhealthy environmental conditions may affect calves' growth and, more in general, their correct development in terms of both morphological and productive performances. Currently, an increasing branch of the computer science and metrology literature is dealing with the automatic measurement of morphological features in cattle via 2D and 3D vision-based techniques to predict their live weight using machine learning- and deep learning-based approaches, thus overcoming all the intrinsic limitations of conventional manual scoring techniques e.g., labour intensive, highly subjective, results often inaccurate and inconsistent [12]-[14].

Among the most recent works concerning dairy cows, a 3D full-body scanning device was used by [15] for monitoring morphology and growth, as well as to estimate indicators such as body volume, surface area and body weight. Measured weights were then compared with those predicted from regression models based on volume, area or morphological traits determined from 3D images. 3-dimensional cameras positioned to view the cow from the top, right side, and rear were used by [16] to implement an automated BCS classification. Further, an

automatic visual detection and biometric identification of individual Holstein-Friesians via convolutional neural networks (CNNs) and deep metric learning techniques was discussed by [17], while [18] deployed a Mask-RCNN segmentation algorithm to segment the images of heifers, as input to a CNN model developed on the Keras platform to predict their body mass. A 3D surface reconstruction and body size measurement system based on multi-view RGB-D cameras was instead developed by [19] using Kinect depth cameras to obtain the point clouds of freely walking pigs from three different views (i.e., upper view, left-view and right-view).

## 3. PAPER CONTRIBUTION

### 3.1. Experimental design

The trial lasted 90 days (13 weeks, from T00 to T13) and was carried out in the period June-September 2022 in an Italian Mediterranean buffalo farm, located in Serre (province of Salerno, Campania Region). A longitudinal observational study was conducted on 30 female buffalo calves, from their birth up to the weaning phase [20]. To predict body weight, for each of them every week the following three biometric measurements were taken, according to the methods suggested by e.g., [21] (see Figure 1):

- height at the withers (WH): vertical distance between the withers (highest point of the back, between the neck and shoulder blades) and the ground;
- body length (BL): oblique distance between the tip of the buttock (apophysis of the ischium) and the tip of the shoulder (shoulder joint);
- chest girth (CG): minimum value measured just behind the shoulders.

Manual measures were performed using a wooden tape for WH, and a roll tape for BL and CG. Two Intel® RealSense™ cameras (D415 Depth camera, and L515 LiDAR camera) along with a RICOH® WG-60 photo camera, were used for measuring WH and BL – in this first set up of the observational study, CG measures could only be made with the photo camera, and manually.

To perform as many noiseless measures as possible, the calves were entered in a containing structure specifically created to keep them stationary. The tip of the shoulder, the apophysis of the ischium, and the withers were coloured using a white spray, to rely on reference points for the image analysis phase, because of the black colour of the buffalo mantle. The containing structure was built considering, besides the availability of spaces, the possibility to take photos and make video recordings while minimizing the incidence of natural light as source of noise for the image analysis process.




Figure 1. In vivo body measurement for Mediterranean Buffalo calves.

### 3.2. Smart cameras setup

To use the RICOH photo camera in an as steady and effective as possible way, it was placed at a fixed distance (about 5 m) from the animal, resting on a photographic tripod. Such distance resulted as the optimal compromise between a number of factors: on the one hand, it was necessary to reduce the impact of sunlight; on the other hand, the camera needed to be levelled before taking the photographs, so to match the degree of inclination of the platform the calves rested upon (on the vertical and horizontal planes, and the 45° angle), with the same inclination degree as the camera; the “x2” zoom factor was set.

The “ImageJ” open–source software was then used for processing the analysis of the 2D images taken to obtain the measures for WH, BL, and CG (Figure 2). For what concerns the D415 Depth Camera and the L515 LiDAR camera, the features of Intel RealSense technology related to sensing and depth perception capabilities, were exploited. Since RealSense products are supported by a specific Software Development Kit (SDK) and a cross-platform library for third-party software developers, a script was developed to make the measurements using the cameras’ hardware.

The software used for the script, including the one to build the libraries, were Visual Studio 2019 and CMake. The main libraries used were instead the Intel library “librealsense2.lib” and the OpenGL library “glfw3.lib”. The main structure of the script is divided into a video processing thread, and a rendering thread. The former retrieves data from the camera in use and provides the data to the latter.

The cameras were adhered to a laptop via strips of adhesive Velcro, and then connected to it with a USB cable, to make possible for the operator to make an as effective as possible video recording surrounding the animal examined. To record the entire body of the single calf, (i) the L500 depth sensor and the RGB camera were activated for the L515 LiDAR Camera (Figure 3), and (ii) the stereo module and the RGB camera were activated for the D415 Depth Camera (Figure 4).

Once made the recordings, the “IntelRealSense Viewer” program was used to model the 3D image, and then carry out the measures for WH and BL.

### 3.3. Data analysis

Three different models – that is Multiple Linear and Polynomial Regression (MLR/MPR), and Artificial Neural Network (ANN) – were implemented (and compared) to predict the progression of calves’ body weight during the trial, starting from the body measurements taken. R Studio and Excel Statistical software were used for the analysis.



Figure 2. Example of measure of BL using ImageJ from a picture taken with the RICOH photo camera. The animal is in a containing structure, and the white dots are made to make the measures possible.




Figure 3. Example of recording via L515 LiDAR Camera.




Figure 4. Example of recording via D415 Depth Camera.

The general model of MLR uses the following equation:

$$y = \beta_0 + \beta_1 x_1 + \beta_2 x_2 + \dots + \beta_k x_k + \varepsilon. \quad (1)$$

A quadratic model was chosen to implement MPR, to prevent conditions of data overfitting, as reported in the following equation:

$$y = \beta_0 + \beta_1 x + \beta_2 x^2 + \varepsilon. \quad (2)$$

In both cases are:  $y$  = variable value;  $\beta_0$  = intercept;  $\beta_k$  =  $k$ -th–regression coefficient;  $\varepsilon$  = standard estimation error.

For what concerns the neural network, a perceptron multilayer network with backpropagation was used. The ANN consisted of input, one hidden and one output layers. The number of nodes of the input layer corresponds to the number of variables describing the calves’ body features tested; the number of neurones in the output layer equals the number of classes (that is the number of calves involved in the study).

To evaluate the reliability of the measurements systems deployed, that is in other words to formalize and test the reliability of the “smart cameras–based monitoring protocol”, the following goodness-of-fit criteria were used [22]:

- Relative Error (RE) between the (manual) benchmark measure and the one obtained with each of the three cameras:

$$RE = \left| \frac{\overline{\text{manual value}} - \overline{\text{camera value}}}{\overline{\text{manual value}}} \right|$$

- Standard Error (SE):

$$SE = \frac{\text{standard deviation of the sample}}{\sqrt{\text{population size}}} = \frac{\sigma}{\sqrt{n}}.$$






Figure 6. MSE (upper) and RMSE (lower) trends for BL.

points are to the bisector, the better the prediction obtained. All the models perform reasonably well: in the linear model the correlation loses some effectiveness at the top of the distribution, likely because of the heavier calves; comparable results are inferred instead for the other two models.

Table 3 shows Pearson's  $R$  and  $R^2$  values for each of the models: the closer the value is to 1, the better the prediction provided. Besides the manual measurements, the best prediction is the one performed by means of ANN, starting from the measurements taken with the Stereo camera D415.

Table 3. Pearson's  $R^2$  Goodness-of-Fit.

Model	Pearson's $R$	Pearson's $R^2$
manuale_poly	0.962	0.925
manuale_nn	0.961	0.924
dstereo_nn	0.961	0.924
manuale_lm	0.958	0.918
dstereo_poly	0.954	0.910
dstereo_lm	0.950	0.903
camera_nn	0.943	0.889
camera_poly	0.942	0.887
camera_lm	0.935	0.874

## 5. DISCUSSION AND CONCLUSIONS

Setting up an automated (and contactless) method to perform body measurements, and predict the progression of body weight, is a long-desired application for the animal production systems.

The results of the longitudinal observational study described in the paper witness about the reliability of using low-cost smart cameras for unobtrusive direct/indirect monitoring of biometric parameters for the estimation of body conditions on Mediterranean Buffalo populations – the average cost for a stereo camera and a photo camera, is about 230 Euros, and the average cost of a LiDAR camera is about 520 Euros. More specifically, the best overall performances were obtained with D415 Depth camera. A similar score was observed for L515 LiDAR camera too, although a lesser number of measurements were taken, due to the two main limitation factors that affected the experiment, that is: (i) continuous movements of the animals, that resulted in a poor vision of the reference point on the calves' body (drawn with the white spray), and therefore in the impossibility of pointing the mouse on them during the image processing phase; and (ii) good functioning of L515 camera compromised in situations of strong light, which again made it




Figure 7. BW prediction using MLR (lm, left column), MPR (poly, center), and ANN (nn, right column).

quite difficult the identification on the video of the reference points. Further, the use of the photo camera provided a valid support because, although of course shooting 2D pics, resulted the least affected from the mentioned limitation factors. Rooms for improvement are anyway possible to overcome the experienced issues, which will be tackled in future steps of this line of research.

The experience conducted shows that, while on the one hand animal health (to which dairy farming broadly relates) is playing a critical role as to the general re-thinking of Public Health [25], on the other hand the continuous improving of the Smart Farming sector, also through the digitalization of livestock farming activities, is meant to widen Public Health Informatics policies and strategies [1], [3]. Also worth mentioning, under an epidemiological point of view, that initiatives are being conducted in PLF focused on the use of smart cameras for detecting specific health conditions (see e.g. [26]).

Accordingly, the “P” for Public in PHI is called to also comprise the concepts of: (i) Precision – improvement of the whole Farming Data Management set, and to figure out accordingly “data-driven”-like business models [6]; Personalized – the ‘per animal approach’, as the timely management of the smallest manageable production unit’s temporal variability [27]; and Predictive – use of AI-related techniques on animal data, to improve human quality of life [28].

An effective monitoring of dairy cattle can positively affect (i) human health, thanks to a better supply chain control [29]), and (ii) environmental health, as pairing weight control with nutrition management can lead to an improvement of animals’ eating habits, to reduce their emissions of Green House Gases (GHG) [30] – in this regard, Kumari’s approach that employs a system dynamic model to link the estimation of methane emissions to different types of consequences, is of particular interest [31]. More in general, initiatives like the one described in the present work can address human, animal, and environmental systems’ needs and challenges, collecting data and selecting timely metrics to assess expected/unexpected outcomes and effects, thus perfectly matching with the One (Digital) Health framework requirements and proposals [32]-[34].

## REFERENCES

- [1] J. A. Magnuson, B. E. Dixon (Eds.), *Public health informatics and information systems*, Springer Nature, 2020, ISBN 978-1-4471-4236-2.
- [2] P. W. O’Carroll, Introduction to public health informatics, in: *Public health informatics and information systems*. P. W. O’Carroll, W. A. Yasnoff, M. E. Ward, L. H. Ripp, E. L. Martin (Eds.). New York: Springer, 2002, ISBN 978-1-4471-4236-2, pp. 1-15.
- [3] W. Hersh, Public Health Informatics in the Larger Context of Biomedical and Health Informatics, in: *Public health informatics and information systems*. J. A. Magnuson, B. E. Dixon (Eds.). Springer Nature, 2020, pp.31-41, ISBN 978-1-4471-4236-2.
- [4] S. Neethirajan, B. Kemp, Digital livestock farming, *Sensing and Bio-Sensing Research* 32 (2021), 100408. DOI: [10.1016/j.sbsr.2021.100408](https://doi.org/10.1016/j.sbsr.2021.100408)
- [5] Y. Zhou, W. Tiemuer, L. Zhou, Bibliometric analysis of smart livestock from 1998-2022, *Procedia Computer Science* 214 (2022), pp. 1428-1435. DOI: [10.1016/j.procs.2022.11.327](https://doi.org/10.1016/j.procs.2022.11.327)
- [6] L. Angrisani, A. Amato, F. Amato, M. A. Autiello, F. Bonavolontà, R. Matera, G. Neglia, N. Piscopo, O. Tamburis, BUFF4L.0: Veterinary and Engineering Sciences at the crossroads in the Industry 4.0 age, Proc. of 2021 IEEE 6th International Forum on Research and Technology for Society and Industry (RTSI), Naples, Italy, 6-9 September 2021, pp. 137-141. DOI: [10.1109/RTSI50628.2021.9597308](https://doi.org/10.1109/RTSI50628.2021.9597308)
- [7] M. F. Hansen, M. L. Smith, L. N. Smith, K. A. Jabbar, D. Forbes, Automated monitoring of dairy cow body condition, mobility and weight using a single 3D video capture device, *Computers in industry* 98 (2018), pp. 14-22. DOI: [10.1016/j.compind.2018.02.011](https://doi.org/10.1016/j.compind.2018.02.011)
- [8] V.A.M. Weber, F. de Lima Weber, A. da Silva Oliveira, G. Astolfi, G. Vilharva Menezes, J. V. de Andrade Porto, F. P. C. Rezende, P. H. de Moraes, (+ 8 more authors), Cattle weight estimation using active contour models and regression trees Bagging, *Computers and Electronics in Agriculture* 179 (2020), 105804. DOI: [10.1016/j.compag.2020.105804](https://doi.org/10.1016/j.compag.2020.105804)
- [9] A. Borghese, B. Moiola, Buffalo: Mediterranean region, Reference Module in Food Science, 2016. DOI: [10.1016/B978-0-08-100596-5.21232-8](https://doi.org/10.1016/B978-0-08-100596-5.21232-8)
- [10] O. Ağyar, C. Tırnk, H. Önder, U. Şen, D. Piwczynski, E. Yavuz, Use of Multivariate Adaptive Regression Splines Algorithm to Predict Body Weight from Body Measurements of Anatolian buffaloes in Türkiye, *Animals* 12 (2022), 2923. DOI: [10.3390/ani12212923](https://doi.org/10.3390/ani12212923)
- [11] R. Matera, G. Di Vuolo, A. Coticelli, A. Salzano, G. Neglia, R. Gimmino, D. D’Angelo, S. Biffani, Relationship among milk conductivity, production traits, and somatic cell score in the Italian Mediterranean buffalo, *Animals* 12 (2022), 2225. DOI: [10.3390/ani12172225](https://doi.org/10.3390/ani12172225)
- [12] A. Van Nuffel, I. Zwervaegher, L. Pluym, S. Van Weyenberg, V. M. Thorup, M. Pastel, B. Sonck, W. Saeys, Lameness detection in dairy cows: part 1. How to distinguish between non-lame and lame cows based on differences in locomotion or behavior, *Animals* 5 (2015), pp. 838–860. DOI: [10.3390/ani5030387](https://doi.org/10.3390/ani5030387)
- [13] J. E. Koltjes, J. B. Cole, R. Clemmens, R. N. Dilger, L. M. Kramer, J. Lunney, M. E. McCue, S. McKay, (+ 11 more authors), A vision for development and utilization of high-throughput phenotyping and big data analytics in livestock, *Front. Genet.* 10 (2019), art. No. 1197. DOI: [10.3389/fgene.2019.01197](https://doi.org/10.3389/fgene.2019.01197)
- [14] K. Wurtz, I. Camerlink, R. B. D’Eath, A. Peña Fernández, T. Norton, J. Steibel, J. Siegford, Recording behaviour of indoor-housed farm animals automatically using machine vision technology: A systematic review, *PloS one* 14 (2019), e0226669. DOI: [10.1371/journal.pone.0226669](https://doi.org/10.1371/journal.pone.0226669)
- [15] Y. Le Cozler, C. Allain, C. Xavier, L. Depuille, A. Caillot, (+ 4 more authors), Volume and surface area of Holstein dairy cows calculated from complete 3D shapes acquired using a high-precision scanning system: Interest for body weight estimation, *Computers and Electronics in Agriculture* 165 (2019), 104977. DOI: [10.1016/j.compag.2019.104977](https://doi.org/10.1016/j.compag.2019.104977)
- [16] X. Song, E. A. M. Bokkers, S. Van Mourik, P. G. Koerkamp, P. P. G. Van Der Tol, Automated body condition scoring of dairy cows using 3-dimensional feature extraction from multiple body regions, *Journal of Dairy Science* 102 (2019), pp. 4294-4308. DOI: [10.3168/jds.2018-15238](https://doi.org/10.3168/jds.2018-15238)
- [17] W. Andrew, J. Gao, S. Mullan, N. Campbell, A.W. Dowsey, T. Burghardt, Visual identification of individual Holstein-Friesian cattle via deep metric learning, *Computers and Electronics in Agriculture* 185 (2021), 106133. DOI: [10.1016/j.compag.2021.106133](https://doi.org/10.1016/j.compag.2021.106133)
- [18] R. Dohmen, C. Catal, Q. Liu, Image-based body mass prediction of heifers using deep neural networks, *Biosystems Engineering* 204 (2021), pp. 283-293. DOI: [10.1016/j.biosystemseng.2021.02.001](https://doi.org/10.1016/j.biosystemseng.2021.02.001)
- [19] S. Shuai, Y. Ling, L. Shihao, Z. Haojie, T. Xuhong, L. Caixing, S. Aidong, L. Hanxing, Research on 3D surface reconstruction and body size measurement of pigs based on multi-view RGB-D

- cameras, *Computers and Electronics in Agriculture* 175 (2020), art. No. 105543.  
DOI: [10.1016/j.compag.2020.105543](https://doi.org/10.1016/j.compag.2020.105543)
- [20] C. K. Glidden, B. Beechler, P. E. Buss, B. Charleston, L.-M. de Klerk-Lorist, (+ 6 more authors), Detection of pathogen exposure in African buffalo using non-specific markers of inflammation, *Frontiers in immunology* 8 (2018), 1944.  
DOI: [10.3389/fimmu.2017.01944](https://doi.org/10.3389/fimmu.2017.01944)
- [21] Associazione per la Scienza e le Produzioni Animali (A.S.P.A.), *Metodologie relative alla macellazione degli animali di interesse zootecnico e alla valutazione e dissezione della loro carcassa*. ISMEA, Roma, 1991. [in Italian].
- [22] W. Grzesiak, D. Zaborski, Examples of the use of data mining methods in animal breeding, in: *data mining applications in engineering and medicine*. A. Karahoca, (Ed.). IntechOpen: Rijeka, Croatia, 2012, ISBN 978-953-51-0720-0, pp. 303–324.
- [23] A. Tatliyer, The Effects of raising type on performances of some data mining algorithms in lambs, *KSU J. Agric. Nat.* 23 (2020), pp. 772–780.
- [24] J. Stangierski, D. Weiss, A. Kaczmarek, Multiple regression models and Artificial Neural Network (ANN) as prediction tools of changes in overall quality during the storage of spreadable processed Gouda cheese, *European Food Research and Technology* 245 (2019), pp. 2539-2547.  
DOI: [10.1007/s00217-019-03369-y](https://doi.org/10.1007/s00217-019-03369-y)
- [25] C. Bellet, L. Hamilton, J. Rushton, Re-thinking public health: Towards a new scientific logic of routine animal health care in European industrial farming, *Humanities and Social Sciences Communications* 8 (2021), pp. 1-11.  
DOI: [10.1057/s41599-021-00890-y](https://doi.org/10.1057/s41599-021-00890-y)
- [26] A. Amato, F. Amato, L. Angrisani, L. Baroli, F. Bonavolontà, G. Neglia, O. Tamburis, Artificial intelligence-based early prediction techniques in agri-tech domain, *Proc. of the 13th Int. Conf. on Intelligent Networking and Collaborative Systems (INCoS-2021)*, Springer, Cham, Asia University, Taichung, Taiwan, 1-3 September 2021, pp. 42-48.  
DOI: [10.1007/978-3-030-84910-8\\_5](https://doi.org/10.1007/978-3-030-84910-8_5)
- [27] I. Halachmi, M. Guarino, Precision livestock farming: a ‘per animal’ approach using advanced monitoring technologies, *Animal* 10(9) (2016), pp. 1482-1483.  
DOI: [10.1017/s1751731116001142](https://doi.org/10.1017/s1751731116001142)
- [28] O. Tamburis, E. Masciari, C. Esposito, G. Fatone, Data mining for animal health to improve human quality of life: insights from a university veterinary hospital, *Proc. of the 10th Int. Conf. on Data Science, Technology and Applications (DATA) - Vol.1*, Lieusaint, SciTePress, Paris, France, 6-8 July, pp. 157-164.  
DOI: [10.5220/0010517201570164](https://doi.org/10.5220/0010517201570164)
- [29] K. Tekin, B. E. G. Ü. M. Yurdakök Dikmen, H. Kanca, R. Guatteo, Precision livestock farming technologies: Novel direction of information flow, *Ankara Üniversitesi Veteriner Fakültesi Dergisi* 68 (2021).  
DOI: [10.33988/auvfd.837485](https://doi.org/10.33988/auvfd.837485)
- [30] D. Bačėninaitė, K. Džermeikaitė, R. Antanaitis, Global Warming and Dairy Cattle: How to Control and Reduce Methane Emission, *Animals* 12 (2022), 2687.  
DOI: [10.3390/ani12192687](https://doi.org/10.3390/ani12192687)
- [31] S. Kumari, R.P. Dahiya, N. Kumari, I. Sharawat, I. Estimation of methane emission from livestock through enteric fermentation using system dynamic model in India, *Int. Journal of Environmental Research and Development*, 4 (2014), pp. 347-352. Online [Accessed 26 November 2023]  
[https://www.ripublication.com/ijerd\\_spl/ijerdv4n4spl\\_13.pdf](https://www.ripublication.com/ijerd_spl/ijerdv4n4spl_13.pdf)
- [32] A. Benis, O. Tamburis, C. Chronaki, A. Moen, One digital health: a unified framework for future health ecosystems, *Journal of Medical Internet Research*, 23 (2021), e22189.  
DOI: [10.2196/22189](https://doi.org/10.2196/22189)
- [33] A. Benis, M. Haghi, T. M. Deserno, O. Tamburis, One digital health intervention for monitoring human and animal welfare in smart cities: viewpoint and use case, *JMIR Med Inform* 11 (2023), e43871.  
DOI: [10.2196/43871](https://doi.org/10.2196/43871)
- [34] O. Tamburis, R. Matera, A. Salzano, A. Calamo, D. Vistocco, G. Neglia, ‘Smart’ buffalo weight estimation via digital technologies: experiences from South Italy, *Stud Health Technol Inform* 302 (2023), pp. 895-896.  
DOI: [10.3233/SH11230298](https://doi.org/10.3233/SH11230298)